



SECURE FIT



COMFORTABLE  
STRETCH



CUT RESISTANCE

## CUT E SLEEVES



### FEATURES

- High stretch nylon material with 4-way stretch points to fit users' arms.
- Tapered design, wider on the bicep and tight on the wrist, to fit the natural arm form.
- Elastic band with non-slip dots on the bicep and stretch wrist cuff to keep the sleeves in place and prevent them from sagging.
- Breathable and lightweight material provides good dexterity and all-day comfort.
- Elastic thumb loop avoids pressure points when using gloves.
- Sun UV rays protection with UPF 50+ according to BS EN 13758-1:2002 +A1:2006 for the covered part of the arms.
- European Certified for cut protection: EN ISO 21420, EN388:2016 (3X42E), UKCA.

### TECHNICAL INFORMATION

#### CUT LEVEL (COLOR CODE):

CUT LEVEL E (RED)

#### COLOR OF THE GLOVE:

GREY

#### MATERIAL:

HPPE, POLYESTER, GLASS FIBER, STEEL FIBER, SPANDEX, ELASTIC YARN

#### GAUGE:

13

#### SIZE RANGE:

CUT C SLEEVES - AVAILABLE IN SIZES 40CM AND 45CM

### UNIT GUIDE

DESCRIPTION	PACK QUANTITY	ARTICLE NUMBER
CUT E SLEEVES - 40CM	1	4932479936
CUT E SLEEVES - 45CM	1	4932479937



**STAY SAFE.**  
**STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeetool.eu



## CUT E SLEEVES

### CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,  
MAXIMUM WASHING  
TEMPERATURE 40° CELSIUS



NO CHEMICAL  
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER

### STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

### USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

### PERIOD OF OBSOLESCENCE


Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.**  
**STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
[milwaukee.tool.eu](http://milwaukee.tool.eu)



18 GAUGE



CUT RESISTANCE



SMARTSWIPE™

# HI-DEX CUT B GLOVES



## FEATURES

- 18 gauge material for extra dexterity and total mobility for precise task.
- Lightweight and thin gloves with polyurethane dipped palm.
- Excellent breathability and all-day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTSWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- 5 times washable allowing extended lifetime, cost and waste reduction.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3242B), UKCA, EAC, Ukraine.

## TECHNICAL INFORMATION

### CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="555327"

### COLOR OF THE GLOVE:

RED

### MATERIAL:

HPPE, POLYESTER, NYLON, GLASS FIBER, SPANDEX.

COATING: POLYURETHANE (PU). REINFORCEMENT: NITRILE

### GAUGE:

18

### SIZE RANGE:

HI-DEX CUT B GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	NO. OF PAIRS	ARTICLE NUMBER	NO. OF PAIRS
7 / S	4932480491	1	4932480506	12
8 / M	4932480492	1	4932480507	12
9 / L	4932480493	1	4932480508	12
10 / XL	4932480494	1	4932480509	12
11 / XXL	4932480495	1	4932480510	12



STAY **SAFE.**  
STAY **PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeeetool.eu



# HI-DEX CUT B GLOVES



## CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,  
MAXIMUM WASHING  
TEMPERATURE 40° CELSIUS



NO CHEMICAL  
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## PERIOD OF OBSOLESCENCE


Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.**  
**STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
[milwaukee.tool.eu](http://milwaukee.tool.eu)



18 GAUGE



CUT RESISTANCE



SMARTSWIPE™

# HI-DEX CUT C GLOVES



## FEATURES

- 18 gauge material for extra dexterity and total mobility for precise task.
- Lightweight and thin gloves with polyurethane dipped palm.
- Excellent breathability and all-day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTSWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- 5 times washable allowing extended lifetime, cost and waste reduction.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3342C), UKCA, EAC, Ukraine.

## TECHNICAL INFORMATION

### CUT LEVEL (COLOR CODE):

CUT LEVEL <ATTRIB A="2684" L="10" O="555328"

### COLOR OF THE GLOVE:

RED

### MATERIAL:

RUBY, POLYESTER, NYLON, GLASS FIBER, SPANDEX.

COATING: POLYURETHANE (PU). REINFORCEMENT:

NITRILE

### GAUGE:

18

### SIZE RANGE:

HI-DEX CUT C GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	NO. OF PAIRS	ARTICLE NUMBER	NO. OF PAIRS
7 / S	4932480496	1	4932480511	12
8 / M	4932480497	1	4932480512	12
9 / L	4932480498	1	4932480513	12
10 / XL	4932480499	1	4932480514	12
11 / XXL	4932480500	1	4932480515	12



STAY **SAFE.**  
STAY **PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeeetool.eu



# HI-DEX CUT C GLOVES

## CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,  
MAXIMUM WASHING  
TEMPERATURE 40° CELSIUS



NO CHEMICAL  
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.




**STAY SAFE.  
STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
[milwaukee.tool.eu](http://milwaukee.tool.eu)





18 GAUGE



CUT RESISTANCE



SMARTSWIPE™

# HI-DEX CUT D GLOVES



## FEATURES

- 18 gauge material for extra dexterity and total mobility for precise task.
- Lightweight and thin gloves with polyurethane dipped palm.
- Excellent breathability and all-day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTSWIPE™ fingertips - allows the use of touch screen devices without removing gloves.
- 5 times washable allowing extended lifetime, cost and waste reduction.
- European Certified for cut resistance protection: EN ISO 21420, EN388:2016 (3X42D), UKCA, EAC, Ukraine.

## TECHNICAL INFORMATION

**CUT LEVEL (COLOR CODE):**  
CUT LEVEL <ATTRIB A="2684" L="10" O="555329"

**COLOR OF THE GLOVE:**  
RED

**MATERIAL:**  
NYLON, HPPE, TUNGSTEN, SPANDEX. COATING:  
POLYURETHANE (PU). REINFORCEMENT: NITRILE

**GAUGE:**  
18

**SIZE RANGE:**  
HI-DEX CUT D GLOVES - AVAILABLE FROM SIZE 7/S TO  
11/XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	NO. OF PAIRS	ARTICLE NUMBER	NO. OF PAIRS
7 / S	4932480501	1	4932480516	12
8 / M	4932480502	1	4932480517	12
9 / L	4932480503	1	4932480518	12
10 / XL	4932480504	1	4932480519	12
11 / XXL	4932480505	1	4932480520	12



STAY **SAFE.**  
STAY **PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeeetool.eu



# HI-DEX CUT D GLOVES

## CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,  
MAXIMUM WASHING  
TEMPERATURE 40° CELSIUS



NO CHEMICAL  
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.  
STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
[milwaukee.tool.eu](http://milwaukee.tool.eu)





CUT RESISTANCE



WINTER



DEXTERITY

# WINTER CUT B GLOVES



## FEATURES

- Winter insulation and dual acrylic liner will keep the hand warm while working in cold conditions.
- Good grip performance in wet conditions due to the latex palm dipping and breathable back of hand.
- 15 Gauge in the outer liner and 10 gauge in the inner liner, allowing good dexterity.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (2242B), EN511 (X1X), UKCA, EAC, Ukraine.

## TECHNICAL INFORMATION

**CUT LEVEL (COLOR CODE):**  
CUT LEVEL <ATTRIB A="2684" L="10" O="689133"

**COLOR OF THE GLOVE:**  
RED

**MATERIAL:**  
OUTER LINER: HPPE, GLASS FIBER, NYLON ELASTIC FIBER. INNER LINER: ACRYLIC TERRY. COATING: LATEX

**GAUGE:**  
15,10

**SIZE RANGE:**  
WINTER CUT B GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	PACK QUANTITY	ARTICLE NUMBER	PACK QUANTITY
7 / S	4932480601	1	4932480606	12
8 / M	4932480602	1	4932480607	12
9 / L	4932480603	1	4932480608	12
10 / XL	4932480604	1	4932480609	12
11 / XXL	4932480605	1	4932480610	12



STAY **SAFE.**  
STAY **PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeetool.eu



# WINTER CUT B GLOVES

## CARE INSTRUCTIONS



DO NOT IRON



NO CHEMICAL  
CLEANING



NO TUMBLER



DO NOT BLEACH



NO WASHING

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.  
STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
[milwaukeeetool.eu](http://milwaukeeetool.eu)



CUT RESISTANCE



WINTER



DURABILITY

# WINTER CUT D GLOVES



## FEATURES

- Winter insulation and dual acrylic liner will keep the hand warm while working in cold conditions.
- Improved water permeability in wet environments due to a ¾ double latex dipping on palm and fingers.
- 15 Gauge in the outer liner and 10 gauge in the inner liner, allowing good dexterity.
- European Certified for cut and cold resistance protection: EN ISO 21420, EN388:2016 (3X43D), EN511 (X1X), UKCA, EAC, Ukraine.

## TECHNICAL INFORMATION

**CUT LEVEL (COLOR CODE):**  
CUT LEVEL <ATTRIB A="2684" L="10" O="689134"

**COLOR OF THE GLOVE:**  
RED

**MATERIAL:**  
OUTER LINER: HPPE, GLASS FIBER, STEEL WIRE,  
ELASTIC FIBER. INNER LINER: ACRYLIC TERRY.  
COATING: LATEX

**GAUGE:**  
15,10

**SIZE RANGE:**  
WINTER CUT D GLOVES - AVAILABLE FROM SIZE 7/S TO 11/XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	PACK QUANTITY	ARTICLE NUMBER	PACK QUANTITY
7 / S	4932480611	1	4932480616	12
8 / M	4932480612	1	4932480617	12
9 / L	4932480613	1	4932480618	12
10 / XL	4932480614	1	4932480619	12
11 / XXL	4932480615	1	4932480620	12



STAY **SAFE.**  
STAY **PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeetool.eu



# WINTER CUT D GLOVES

## CARE INSTRUCTIONS



DO NOT IRON



NO CHEMICAL  
CLEANING



NO TUMBLER



DO NOT BLEACH



NO WASHING

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.  
STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.


Techtronic Industries GmbH  
71364 Winnenden  
Germany  
[milwaukee.tool.eu](http://milwaukee.tool.eu)



CUT RESISTANCE



SMARTWIPE™



18 GAUGE



REINFORCEMENT

# HIGH CUT F GLOVES



## FEATURES

- Highest European cut level protection.
- 18 gauge material for extra dexterity.
- Excellent grip performance with nitrile dipped palm, material performs better than other materials in wide range of temperatures and oily surfaces.
- Excellent breathability and all day comfort.
- Nitrile reinforcement between thumb and index finger for more durability.
- SMARTWIPE™ palm and fingertips - allows the use of touch screen devices without removing gloves.
- DMF free and REACH compliance.
- 3 times machine washable.
- European Certified for cut protection: EN ISO 21420 and EN388:2016 (4X43F).

## TECHNICAL INFORMATION

### CUT LEVEL (COLOR CODE):

CUT LEVEL F (PURPLE)

### COLOR OF THE GLOVE:

PURPLE

### MATERIAL:

HPPE, NYLON, TUNGSTEN, GLASS FIBER, SPANDEX.  
COATING: NITRILE, SANDY FINISH. REINFORCEMENT:  
NITRILE

### GAUGE:

18

### SIZE RANGE:

HIGH CUT F GLOVES - AVAILABLE FROM SIZE 7/S TO 11/  
XXL

## UNIT GUIDE

SIZE	ARTICLE NUMBER	PACK QUANTITY	ARTICLE NUMBER	PACK QUANTITY
7 / S	4932492040	1	4932492045	12
8 / M	4932492041	1	4932492046	12
9 / L	4932492042	1	4932492047	12
10 / XL	4932492043	1	4932492048	12
11 / XXL	4932492044	1	4932492049	12



**STAY SAFE.  
STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeeetool.eu





# HIGH CUT F GLOVES



## CARE INSTRUCTIONS



WASHING, NORMAL PROCESS,  
MAXIMUM WASHING  
TEMPERATURE 40° CELSIUS



NO CHEMICAL  
CLEANING



DO NOT IRON



DO NOT BLEACH



NO TUMBLER

## STORAGE INSTRUCTIONS

Keep in its original packaging, under normal temperature and humidity conditions and in clean, covered and ventilated premises. Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion. Storage temperature: -5°C to 35°C. Storage humidity: 20%-75%

## USAGE INSTRUCTIONS

Do not wear gloves when in the vicinity of rotating machine parts (saw blades, drills etc.) Risk of entanglement! The product will not protect against chemicals, handling of hot or cold or cold objects, very sharp objects which impact the hands with great force or speed. If tear level  $\geq 1$  then do not use near to moving machinery-entanglement hazard. This product is designed to minimize risk / provide protection against general mechanical risk.

## PERIOD OF OBSOLESCENCE

Gloves can be used out of the pack 5 years after production date, printed on the glove. Gloves should be used within 3 years after their purchase. Glove life time in use is based on wear and abrasion.



**STAY SAFE.**  
**STAY PRODUCTIVE.**

Disclaimer  
Information present within  
this sheet was correct at  
the date of issue.

Techtronic Industries GmbH  
71364 Winnenden  
Germany  
milwaukeeetool.eu